

GREASE-X Technical Data Sheet

Grease-X[®] 2lb. Jars

Grease-X® Biozime application:

Unscrew lid from the top of the Grease-X° container.



Add the correct amount of Grease-X° granules to warm water per the directions on the jar.



Let the Grease-X® granules sit in water for 15 Minutes to activate the microorganisms.



Pour the Grease-X® granules down the sink that you are treating.



Wait for at least 20 min. before running water down the sink for best results.



To order Grease-X, visit our website at www.RootX.com, or call 1-800-844-4974



THE RIGHT SOLUTION. RIGHT NOW.

For Precautionary Statements and more specific information, please refer to the Grease-X[®] label.



Fat, Oil and Grease Problems

FOG. (fat, oil, grease) can be a real problem for home owners, business owners and business managers. Contaminants such as fats, grease, soap scum, and cellulose can stick to the pipe walls restricting the water flow to the point of causing a blockage and subsequent back-up. In grease traps grease build can cause a smelly mess. Back-ups are embarrassing and can be costly when interceptors have to be pumped more to prevent odors and failures. Now, through biotechnology, there is a reliable and easy to use treatment that offers a preventative maintenance solution.

The biotechnology solution: Grease-X BIOZYME Microbial Ecosystem

Microorganisms are nature's own method of eliminating organic waste. The specially selected mixtures of live microbes contained in GREASE-X BIOZYME, along with the enzymes they secrete, are well suited to digesting fat, oil, grease (FOG), and other organic matter as it enters and flows through the collection system. The GREASE-X BIOZYME microbes adhere to the collection system lines and lift station walls.

In digesting organic waste, they reproduce and form colonies that continue to consume floating waste and accumulated FOG. The wall coating also acts as a lubricant to help reduce back-ups. The by-products of microbial digestion are perfectly natural, environmentally safe substances like carbon dioxide and water.

PRODUCT DESCRIPTION:

GREASE-X BIOZYME is a highly concentrated microbial ecosystem containing specialized natural microorganisms selected for maximum efficiency in the biodegradation of organic contaminants in industrial and Residential Sewer. It is supplied as a dry fine granule, packaged in 2 lb jars for ease of use.

Benefits of Grease-X Usage:

- Maintains free flowing collection systems.
- Reduces the floating FOG blanket and accumulation of grease on pipe and grease trap walls.
- Saves businesses money versus mechanical and chemical line cleaning.
- Environmentally friendly approach.
- Contains no hazardous caustic, surfactants or solvents.
- Supplied in dry granular form for optimum stability.

To order Grease-X, visit our website at www.RootX.com, or call 1-800-844-4974

